

Optimum Torque Wrench and Pump Combinations



Optimum Torque Wrench and Pump Combinations

For optimum speed and performance, Enerpac recommends the following system set-up with wrench-pump-hose combinations. For other combinations, consult your Enerpac bolting expert or your authorized Enerpac distributor.

XC-Series, Battery-Powered Torque Wrench Pumps

The XC-Series Cordless Torque Wrench pump is ideal for maintenance applications in the PowerGen, Oil & Gas and MRO markets. This portable pump is perfect for remote locations, sites that do not have access to power or where trip hazards are a concern.

PMU-Series, Electric Torque Wrenches

Portable lightweight pump with standard heat exchanger. Universal motor for high power-to-weight ratio. Generates full pressure on as little as 50% of the rated line voltage.

TQ-700 Series Electric Wrench Pumps

Designed for both portability and production, the TQ-700 features optimized flow technology to deliver superior bolting speed.

ZU4T-Series, Electric Wrench Pumps

Utilizing a universal motor, the ZU4-Series has excellent low voltage characteristics. It works well with long extension cords or generator-driven electrical power supplies.













ZE4T, ZE5T-Series Electric Wrench Pumps

The ZE-Series features premium options, such as the LCD to display torque or pressure values, and self-diagnostics. These pumps utilize an induction motor, making the ZE-Series the coolest and quietest pumps in their class.

ZA-Series Air Driven Torque Wrench Pump

Utilizing the highly efficient design of the Z-Class pumping element, this air driven pump is best suited to power medium to large size torque wrenches.

Torque Wrench Pumps

	ELECTRIC PUMPS					AIR DRIVEN PUMPS
	XC-Series	PMU-Series	TQ-Series	ZU4-Series	ZE-Series	ZA4-Series
						
Flow at 10,000 psi:	15 in ³ /min	20 in ³ /min	30 in ³ /min	60 in ³ /min	60-120 in ³ /min	60 in ³ /min
Reservoir Capacity:	.5 Gallon	.5 - 1 Gallon	1 Gallon	1 - 1.75 Gallon	1 - 10 Gallon	1 - 1.75 Gallon
Weight:						
Model Number: 1) 115 V, 1-ph 2) 230 V, 1-ph 3) 230 V, 3-ph 4) 400 V, 3-ph	XC-1502TB ¹⁾ XC-1502TE ²⁾	PMU-10427-Q ¹⁾ PMU-10447-Q ¹⁾ PMU-10422-Q ²⁾ PMU-10442-Q ²⁾	TQ-700 B ¹⁾ TQ-700 E ²⁾	ZU4204TB-Q ¹⁾ ZU4208TB-Q ¹⁾ ZU4204TE-Q ²⁾ ZU4208TE-Q ²⁾ ZU4204BB-QH ¹⁾ ZU4204BB-Q ¹⁾ ZU4208BE-QH ²⁾ ZU4204BE-Q ²⁾	ZE4204TB-QHR ¹⁾ ZE4204TE-QHR ²⁾ ZE4204TG-QHR ³⁾ ZE5204TW-QHR ⁴⁾	ZA4208TX-QRU105 ZA4204TX-Q ZA4208TX-Q ZA4204TX-QR ZA4208TX-QR



Represented By:

#30, 3250 - 51 Ave NW
Edmonton, Alberta
Canada T6P 0E1

M: 780.469.6002
TF: 1.877.742.5367
F: 780.469.3257

www.pickford.com
Afterhours:
780.221.0331